

Recessed Series

Strahman's recessed mixing units are designed to conceal mixing unit piping in a stainless steel box for recessed wall mounting. All exposed parts are either bronze chrome-plated or stainless steel depending on the selected unit. These units are ideal for new construction or other places where concealed piping and good looks are desirable.

Specifications

- ◆ **Maximum recommended operating temperature** 200°F/93°C
- ◆ **Maximum working pressure** 150 psi
- ◆ Recessed Series available for:
M-5000TG/5700TG
M-159/750/159TG/750TG
M-358/758

NOTE: When ordering, specify angle valves (back entry) or globe valves (top entry).

Please see reverse side for dimensions.



Shown: Recessed Series with M-5000TG unit; shown with premium hose assembly and red S-70 Series nozzle



USA Headquarters

2801 Baglyos Circle ♦ Bethlehem, PA 18020

Phone: (484) 893-5080 ♦ Fax: (484) 893-5099 ♦ Toll Free: (877) STRAHMAN

www.strahmanvalves.com

France

Savoie Hexapole, F-73420 Mery, France

Tel: 33 (0) 4 79 35 78 00

Fax: 33 (0) 4 79 35 78 20

Germany

Zum Schwarzhof 14, 77704, Oberkirch, Germany

Tel: 49 (0) 7802 - 7037879

Fax: 49 (0) 7802 - 7037889

Recessed Series Dimensions

