

Top-Flo® 3A Concentric Check Valve



Stainless Steel Flow Control Equipment for the

Food, Beverage, Dairy, Cosmetics, Biotechnology,

Pharmaceutical and Electronics Processing Industries


www.toplineonline.com

Top-Flo® 3A Concentric Check Valve

This finely crafted 316L stainless steel check valve offers maximum quality that meets all 3A standards. With a unique clamp design, a simple twist of the wing nut permits quick disassembly without tools. The stainless steel spring in this superior valve assures positive closure and smooth operation. This valve is designed for vertical as well as horizontal applications.

SIZE	Α	STOCK NO.
1/2"	3-1/2"	384505VA
3/4"	3-1/2"	384507VA
1"	4-1/8"	384510VA
1 1/2"	4-9/16"	384515VA
2"	5-1/16"	384520VA
2 1/2"	5-3/8"	384525VA
3"	6-1/8"	384530VA
4"	8-1/8"	384540VA
6"	8-1/8"	384560VA

T45MP Standard Disc Type Check Valve (3A)



SIZE	Α	STOCK NO.
1/2"	3-1/2"	N/A
3/4"	3-1/2"	N/A
1"	4-1/8"	384510GFEA
1 1/2"	4-9/16"	384515GFEA
2"	5-1/16"	384520GFEA
2 1/2"	5-3/8"	384525GFEA
3"	6-1/8"	384530GFEA
4"	8-1/8"	384540GFEA
6"	8-1/8"	384560GFEA
	1/2" 3/4" 1" 1 1/2" 2" 2 1/2" 3" 4"	1/2" 3-1/2" 3/4" 3-1/2" 1" 4-1/8" 1 1/2" 4-9/16" 2" 5-1/16" 2 1/2" 5-3/8" 3" 6-1/8" 4" 8-1/8"

T45MP
Guide Finger
Disc Type
Check Valve

FEATURES

- Suitable for C.I.P.
- Operating pressure to 150 psi
- Temperature from 30°F min. to 225°F max.
- Standard end connectionclamp type (butt weld & TI-Line upon request)
- Guide finger disc available upon request.
- Standard seals-FDA Viton (EPDM & other elastomers upon request)
- Internal finish-25 to 30ra average
- Material Test Reports provided upon request
- Eccentric Type available upon request
- For steam applications consult factory



... the source for all your product needs in the process industries Contact your Top Line Representative for Assistance

Office: P.O. Box 264 · Bradford, PA 16701

Plant: 21 Valley Hunt Drive · Lewis Run, PA 16738

Phone: 800-458-6095

814-362-4626

Fax: 814-362-4453